



WOOD

Description

PrintaMent WOOD (wood filled PLA) is an easy to print filament with great optics, haptics and smell. Due to the high content of wood, PrintaMent WOOD is very easy to post process with e.g. sanding and varnishing. For PrintaMent WOOD we recommend a printbed coated with PrintaFix and a nozzle with at least 0.5mm. Attention: due to the high wood content, this material is very abrasive and should be printed with a hardened nozzle, otherwise your brass nozzle will wear out very quickly.

Applications

- 3D prints with a look and feel like wood
- 3D prints that you want to sand and postprocess

Printing Settings

- Adhesion agent: PrintaFix
- Printing temperature: 200°C-215°C
- Heated printbed: not needed when using PrintaFix

Cheat sheets for major 3D printers can be found at: www.aprintapro.com/manual#PrintaMent

Additional Information

All PrintaMent Filaments are produced in Europe using modern production standards: During production, the latest laser measuring technology is used to ensure that you are receiving a spool of filament with a very tight diameter and roundness tolerance. Most materials offer a wide selection of beautiful colors, providing you with plenty of options to perfect and individualize prints. PrintaMent is available in the diameters 1.75mm and 2.85mm and comes on a transparent spool which makes it easy to see how much filament is left on the reel. The PrintaMent Box has an indication window to show how much Filament is left on the reel. Store PrintaMent in a cool and dry environment, away from UV light to enhance the shelf life.